

**Trade name:** SEAM GRIP +WP**Current version :** 3.1.0, issued: 15.01.2019**Replaced version:** 3.0.0, issued: 10.01.2019**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****SEAM GRIP +WP****Product Item Code: 11541, 004000, 10515, 10592****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Adhesive and sealant for flexible repairs.

**Uses advised against**

No data available.

**1.3 Details of the supplier of the safety data sheet****Address**McNett Europe  
Saarstrasse 5  
29664 Walsrode

Telephone no. +49 (0)5161-41805-0

Fax no. +49 (0)5161-418-0511

**Advice on Safety Data Sheet**

sdb\_info@umco.de

**1.4 Emergency telephone number**

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**Eye Irrit. 2; H319  
Flam. Liq. 3; H226  
Resp. Sens. 1; H334  
Skin Irrit. 2; H315  
STOT RE 2; H373  
STOT SE 3; H335**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07



GHS08

**Signal word**

Danger

**Trade name:** SEAM GRIP +WP

**Current version :** 3.1.0, issued: 15.01.2019

**Replaced version:** 3.0.0, issued: 10.01.2019

**Region:** GB

**Hazardous component(s) to be indicated on label:**

xylene  
diphenylmethane-4,4'-di-isocyanate

**Hazard statement(s)**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure

**Hazard statements (EU)**

EUH204	Contains isocyanates. May produce an allergic reaction.
EUH208	Contains tosyl isocyanate. May produce an allergic reaction.

**Precautionary statement(s)**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P370+P378	In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

**Supplemental label elements**

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.  
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.  
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

**2.3 Other hazards**

No data available.

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

**SECTION 3: Composition/information on ingredients**

**3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures**

**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	<b>xylene</b>		
	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	STOT RE 2; H373 Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Acute Tox. 4; H332	>= 25.00 - < 50.00 %-b.w.
2	<b>ethylbenzene</b>		
	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Acute Tox. 4*; H332 Asp. Tox. 1; H304 Flam. Liq. 2; H225 STOT RE 2; H373	>= 5.00 - < 10.00 %-b.w.
3	<b>diphenylmethane-4,4'-di-isocyanate</b>		
	101-68-8 202-966-0 615-005-00-9 01-2119457014-47	Acute Tox. 4; H332 Carc. 2; H351 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT RE 2; H373i STOT SE 3; H335	< 2.50 %-b.w.
4	<b>tosyl isocyanate</b>		
	4083-64-1 223-810-8 615-012-00-7 -	EUH014 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Irrit. 2; H315 STOT SE 3; H335	< 0.50 %-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(\* , \*\* , \*\*\* , \*\*\*\* ) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	C	STOT RE 2; H373: C >= 10%	-	-
3	C, 2	Resp. Sens. 1; H334: C >= 0.1% Eye Irrit. 2; H319: C >= 5% Skin Irrit. 2; H315: C >= 5% STOT SE 3; H335: C >= 5%	-	-
4	-	Eye Irrit. 2; H319: C >= 5% Skin Irrit. 2; H315: C >= 5% STOT SE 3; H335: C >= 5%	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
2	H373 -; hearing organs; -
3	H373i inhalational; -; -

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. In case of persisting adverse effects, consult a physician.

#### After inhalation

Ensure supply of fresh air. Remove affected person from the immediate area. If unconscious place in recovery position and seek medical advice.

#### After skin contact

When in contact with the skin, clean with soap and water.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get medical attention if pain still persists.

#### After ingestion

Do not induce vomiting. Call a doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam; Carbon dioxide; Extinguishing powder; Water spray jet

#### Unsuitable extinguishing media

High power water jet

### 5.2 Special hazards arising from the substance or mixture

When heating or in case of fire formation of toxic gases. In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO<sub>2</sub>); Nitrogen oxides (NO<sub>x</sub>); Nitrous oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When picked up, treat material as prescribed under heading "Disposal considerations".

### 6.4 Reference to other sections

No data available.

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

#### General protective and hygiene measures

Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke during work time. After worktime and during work intervals the affected skin areas must be thoroughly cleaned. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area.

#### Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention. Keep away from ignition sources and provide for good ventilation. Take precautionary measures against static charges. Vapours can form an explosive mixture with air.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Keep from freezing. Protect from heat and direct sunlight.

#### Requirements for storage rooms and vessels

Containers which are opened must be carefully resealed.

#### Advice on storage assembly

Do not store together with: Acids; Bases; Amines; Alcohols

### 7.3 Specific end use(s)

No data available.

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	<b>xylene</b>	<b>1330-20-7</b>	<b>215-535-7</b>
	<b>2000/39/EC</b>		
	Xylene, mixed isomers, pure		
	WEL short-term (15 min reference period)	442	mg/m <sup>3</sup> 100 ppm
	WEL long-term (8-hr TWA reference period)	221	mg/m <sup>3</sup> 50 ppm
	Skin resorption / sensibilisation	Skin	
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Xylene, o-, m-, p- or mixed isomers		
	WEL short-term (15 min reference period)	441	mg/m <sup>3</sup> 100 ppm
	WEL long-term (8-hr TWA reference period)	220	mg/m <sup>3</sup> 50 ppm
	Comments	Sk, BMGV	
2	<b>ethylbenzene</b>	<b>100-41-4</b>	<b>202-849-4</b>
	<b>2000/39/EC</b>		
	Ethylbenzene		
	WEL short-term (15 min reference period)	884	mg/m <sup>3</sup> 200 ppm
	WEL long-term (8-hr TWA reference period)	442	mg/m <sup>3</sup> 100 ppm
	Skin resorption / sensibilisation	Skin	
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Ethylbenzene		
	WEL short-term (15 min reference period)	552	mg/m <sup>3</sup> 125 ppm
	WEL long-term (8-hr TWA reference period)	441	mg/m <sup>3</sup> 100 ppm
	Comments	Sk	
3	<b>diphenylmethane-4,4'-di-isocyanate</b>	<b>101-68-8</b>	<b>202-966-0</b>
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Isocyanates, all (as -NCO) Except methyl isocyanate		
	WEL short-term (15 min reference period)	0.07	mg/m <sup>3</sup>
	WEL long-term (8-hr TWA reference period)	0.02	mg/m <sup>3</sup>
	Comments	Sen	

#### DNEL, DMEL and PNEC values

##### DNEL values (worker)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	<b>xylene</b>	<b>1330-20-7</b>		<b>215-535-7</b>
	dermal	Long term (chronic)		180 mg/kg/day
	inhalative	Short term (acut)		289 mg/m <sup>3</sup>
	inhalative	Long term (chronic)		77 mg/m <sup>3</sup>

##### DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	<b>xylene</b>	<b>1330-20-7</b>		<b>215-535-7</b>
	oral	Long term (chronic)		1.6 mg/kg/day
	dermal	Long term (chronic)		108 mg/kg/day
	inhalative	Short term (acut)		174 mg/m <sup>3</sup>
	inhalative	Long term (chronic)		14.8 mg/m <sup>3</sup>

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

### PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	xylene		1330-20-7 215-535-7	
	water	fresh water	0.327	mg/L
	water	marine water	0.327	mg/L
	water	fresh water sediment	12.46	mg/kg
	water	marine water sediment	12.46	mg/kg
	soil	-	2.31	mg/kg
	sewage treatment plant	-	6.58	mg/L

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator A2 (DIN EN 14387 / DIN EN 141)

#### Eye / face protection

Safety glasses (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material nitrile rubber  
Material thickness 0.8 mm

#### Other

Chemical-resistant work clothes.

### Environmental exposure controls

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Form/Colour</b>	
pasty	
colourless	
<b>Odour</b>	
characteristic	
<b>Odour threshold</b>	
No data available	
<b>pH value</b>	
No data available	
<b>Boiling point / boiling range</b>	
Value	139 °C

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

<b>Melting point / melting range</b>			
No data available			
<b>Decomposition point / decomposition range</b>			
No data available			
<b>Flash point</b>			
Value	25	°C	
<b>Ignition temperature</b>			
Value	430	°C	
<b>Auto-ignition temperature</b>			
No data available			
<b>Oxidising properties</b>			
No data available			
<b>Explosive properties</b>			
No data available			
<b>Flammability (solid, gas)</b>			
No data available			
<b>Lower flammability or explosive limits</b>			
Value	1.0	% vol	
<b>Upper flammability or explosive limits</b>			
Value	7.8	% vol	
<b>Vapour pressure</b>			
Value	9	hPa	
Reference temperature	20	°C	
<b>Vapour density</b>			
No data available			
<b>Evaporation rate</b>			
No data available			
<b>Relative density</b>			
No data available			
<b>Density</b>			
Value	0.96	g/cm <sup>3</sup>	
Reference temperature	20	°C	
<b>Solubility in water</b>			
Comments	insoluble		
<b>Solubility(ies)</b>			
No data available			
<b>Soluble in</b>			
hydrocarbons			
<b>Partition coefficient: n-octanol/water</b>			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
log Pow		3.12	
Reference temperature		20	°C
Source	ECHA		



Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

Viscosity	
Value	20000 mPa*s
Reference temperature	20 °C
Type	dynamic
Method	Brookfield

Solvent content	
Value	40.0 %

## 9.2 Other information

Other information
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

When heating the product, explosive vapour-air mixtures can be formed.

### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources. Moisture.

### 10.5 Incompatible materials

Acids; Alcohols; Bases; Amines; The product reacts slowly with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result distortion blowing and in extreme cases bursting of the container.

### 10.6 Hazardous decomposition products

In case of fire: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
LD50		3523	mg/kg bodyweight
Species	rat		
Method	EU Method B.1		
Source	ECHA		

Acute dermal toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	SEAM GRIP +WP Product Item Code: 11541, 004000, 10515, 10592
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

Acute dermal toxicity	
No data available	

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	SEAM GRIP +WP Product Item Code: 11541, 004000, 10515, 10592
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
LC50		6700	ppmV
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	EU Method B.2		
Source	ECHA		

Skin corrosion/irritation	
No data available	

Serious eye damage/irritation	
No data available	

Respiratory or skin sensitisation	
No data available	

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
Species		Chinese hamster Ovary (CHO)	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Reproduction toxicity	
No data available	

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
Species		mouse	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

STOT - single exposure	
No data available	

STOT - repeated exposure	
No data available	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Vapours and Mist cause irritation effects to the eyes and the respiratory tract. Has a degreasing effect on the skin.	

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

## SECTION 12: Ecological information

### 12.1 Toxicity

**Toxicity to fish (acute)**

No data available

**Toxicity to fish (chronic)**

No data available

**Toxicity to Daphnia (acute)**

No data available

**Toxicity to Daphnia (chronic)**

No data available

**Toxicity to algae (acute)**

No data available

**Toxicity to algae (chronic)**

No data available

**Bacteria toxicity**

No data available

### 12.2 Persistence and degradability

No data available.

### 12.3 Bioaccumulative potential

**Partition coefficient: n-octanol/water**

No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
	log Pow	3.12	
	Reference temperature	20	°C
	Source	ECHA	

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB assessment

No data available.

### 12.6 Other adverse effects

No data available.

### 12.7 Other information

**Other information**

Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

**Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

**Packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of in agreement with the regional waste disposal company.



Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

**SECTION 14: Transport information**

**14.1 Transport ADR/RID/ADN**

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1133
Proper shipping name	ADHESIVES
Tunnel restriction code	D/E
Label	3
Comments	Containers with a capacity <= 450 ltrs are not subject to ADR-regulations (refer to 2.2.3.1.5.)

**14.2 Transport IMDG**

Class	3
Packing group	III
UN number	UN1133
Proper shipping name	ADHESIVES
EmS	F-E, S-D
Label	3
Comments	Containers with a capacity <= 30 ltrs are not subjected to IMDG regulations, chapter 4.1, 5.2 and 6.1 (see IMDG-Code 2.3.2.5)

**14.3 Transport ICAO-TI / IATA**

Class	3
Packing group	III
UN number	UN1133
Proper shipping name	Adhesives
Label	3

**14.4 Other information**

No data available.

**14.5 Environmental hazards**

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

**14.6 Special precautions for user**

No data available.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not relevant

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulations**

**Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

**REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 3, 40
-----------------------------------------------------------------------------------------	----------

Trade name: SEAM GRIP +WP

Current version : 3.1.0, issued: 15.01.2019

Replaced version: 3.0.0, issued: 10.01.2019

Region: GB

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	diphenylmethane-4,4'-di-isocyanate	101-68-8	202-966-0	56

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category: P5c

**Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)**

VOC content	40	%
VOC-value	384	g/l

**15.2 Chemical safety assessment**

No data available.

**SECTION 16: Other information**
**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

EUH014	Reacts violently with water.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H351	Suspected of causing cancer
H373i	May cause damage to organs through prolonged or repeated exposure if inhaled.

**Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)**

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
2	The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

**Department issuing safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, 21107 Hamburg, Germany

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.  
Prod-ID 633250