

Trade name: AQUASURE+FD**Current version :** 3.0.0, issued: 10.01.2019**Replaced version:** 2.1.0, issued: 14.09.2018**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****AQUASURE+FD****Product Item Code: 10112, 10116, 11146, 004002, 10194****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Adhesive for flexible repairs.

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**McNett Europe
Saarstrasse 5
29664 Walsrode

Telephone no. +49 (0)5161-41805-0

Fax no. +49 (0)5161-418-0511

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**Eye Irrit. 2; H319
Flam. Liq. 3; H226
Resp. Sens. 1; H334
Skin Irrit. 2; H315
STOT RE 2; H373
STOT SE 3; H335**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07



GHS08

Signal word

Danger

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

Hazardous component(s) to be indicated on label:

xylene
diphenylmethane-4,4'-di-isocyanate

Hazard statement(s)

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure

Hazard statements (EU)

EUH204	Contains isocyanates. May produce an allergic reaction.
EUH208	Contains tosyl isocyanate. May produce an allergic reaction.

Precautionary statement(s)

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P370+P378	In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

Supplemental label elements

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

No data available.

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	xylene		
	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	STOT RE 2; H373 Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Acute Tox. 4; H332	>= 10.00 - < 25.00 %-b.w.
2	ethylbenzene		
	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Acute Tox. 4*; H332 Asp. Tox. 1; H304 Flam. Liq. 2; H225 STOT RE 2; H373	>= 5.00 - < 10.00 %-b.w.
3	diphenylmethane-4,4'-di-isocyanate		
	101-68-8 202-966-0 615-005-00-9 01-2119457014-47	Acute Tox. 4; H332 Carc. 2; H351 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT RE 2; H373i STOT SE 3; H335	< 2.50 %-b.w.
4	tosyl isocyanate		
	4083-64-1 223-810-8 615-012-00-7 -	EUH014 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Irrit. 2; H315 STOT SE 3; H335	< 0.50 %-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(* , ** , *** , ****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	C	STOT RE 2; H373: C >= 10%	-	-
3	C, 2	Resp. Sens. 1; H334: C >= 0.1% Eye Irrit. 2; H319: C >= 5% Skin Irrit. 2; H315: C >= 5% STOT SE 3; H335: C >= 5%	-	-
4	-	Eye Irrit. 2; H319: C >= 5% Skin Irrit. 2; H315: C >= 5% STOT SE 3; H335: C >= 5%	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
2	H373 -; hearing organs; -
3	H373i inhalational; -; -

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. In case of persisting adverse effects, consult a physician.

After inhalation

Ensure supply of fresh air. Remove affected person from the immediate area. If unconscious place in recovery position and seek medical advice.

After skin contact

When in contact with the skin, clean with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get medical attention if pain still persists.

After ingestion

Do not induce vomiting. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Carbon dioxide; Extinguishing powder; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

When heating or in case of fire formation of toxic gases. In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Nitrogen oxides (NO_x); Nitrous oxides (NO_x)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When picked up, treat material as prescribed under heading "Disposal considerations".

6.4 Reference to other sections

No data available.

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

General protective and hygiene measures

Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke during work time. After worktime and during work intervals the affected skin areas must be thoroughly cleaned. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention. Keep away from ignition sources and provide for good ventilation. Take precautionary measures against static charges. Vapours can form an explosive mixture with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Keep from freezing. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully resealed.

Advice on storage assembly

Do not store together with: Acids; Bases; Amines; Alcohols

7.3 Specific end use(s)

No data available.

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
	2000/39/EC		
	Xylene, mixed isomers, pure		
	WEL short-term (15 min reference period)	442	mg/m ³ 100 ppm
	WEL long-term (8-hr TWA reference period)	221	mg/m ³ 50 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	Xylene, o-, m-, p- or mixed isomers		
	WEL short-term (15 min reference period)	441	mg/m ³ 100 ppm
	WEL long-term (8-hr TWA reference period)	220	mg/m ³ 50 ppm
	Comments	Sk, BMGV	
2	ethylbenzene	100-41-4	202-849-4
	2000/39/EC		
	Ethylbenzene		
	WEL short-term (15 min reference period)	884	mg/m ³ 200 ppm
	WEL long-term (8-hr TWA reference period)	442	mg/m ³ 100 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	Ethylbenzene		
	WEL short-term (15 min reference period)	552	mg/m ³ 125 ppm
	WEL long-term (8-hr TWA reference period)	441	mg/m ³ 100 ppm
	Comments	Sk	
3	diphenylmethane-4,4'-di-isocyanate	101-68-8	202-966-0
	List of approved workplace exposure limits (WELs) / EH40		
	Isocyanates, all (as -NCO) Except methyl isocyanate		
	WEL short-term (15 min reference period)	0.07	mg/m ³
	WEL long-term (8-hr TWA reference period)	0.02	mg/m ³
	Comments	Sen	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	xylene	1330-20-7		215-535-7
	dermal	Long term (chronic)		180 mg/kg/day
	inhalative	Short term (acut)		289 mg/m ³
	inhalative	Long term (chronic)		77 mg/m ³

DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	xylene	1330-20-7		215-535-7
	oral	Long term (chronic)		1.6 mg/kg/day
	dermal	Long term (chronic)		108 mg/kg/day
	inhalative	Short term (acut)		174 mg/m ³
	inhalative	Long term (chronic)		14.8 mg/m ³

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	xylene		1330-20-7 215-535-7	
	water	fresh water	0.327	mg/L
	water	marine water	0.327	mg/L
	water	fresh water sediment	12.46	mg/kg
	water	marine water sediment	12.46	mg/kg
	soil	-	2.31	mg/kg
	sewage treatment plant	-	6.58	mg/L

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator A2 (DIN EN 14387 / DIN EN 141)

Eye / face protection

Safety glasses (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material nitrile rubber
Material thickness 0.8 mm

Other

Chemical-resistant work clothes.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour	
pasty	
colourless	
Odour	
characteristic	
Odour threshold	
No data available	
pH value	
No data available	
Boiling point / boiling range	
Value	139 °C

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

Melting point / melting range			
No data available			
Decomposition point / decomposition range			
No data available			
Flash point			
Value	25	°C	
Ignition temperature			
Value	430	°C	
Auto-ignition temperature			
No data available			
Oxidising properties			
No data available			
Explosive properties			
No data available			
Flammability (solid, gas)			
No data available			
Lower flammability or explosive limits			
Value	1.0	% vol	
Upper flammability or explosive limits			
Value	7.8	% vol	
Vapour pressure			
Value	9	hPa	
Reference temperature	20	°C	
Vapour density			
No data available			
Evaporation rate			
No data available			
Relative density			
No data available			
Density			
Value	0.98	g/cm ³	
Reference temperature	20	°C	
Solubility in water			
Comments	insoluble		
Solubility(ies)			
No data available			
Soluble in			
hydrocarbons			
Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
log Pow		3.12	
Reference temperature		20	°C
Source		ECHA	

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

Viscosity	
Value	80000 mPa*s
Reference temperature	20 °C
Type	dynamic
Method	Brookfield

Solvent content	
Value	25.0 %

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

When heating the product, explosive vapour-air mixtures can be formed.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources. Moisture.

10.5 Incompatible materials

Acids; Alcohols; Bases; Amines; The product reacts slowly with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result distortion blowing and in extreme cases bursting of the container.

10.6 Hazardous decomposition products

In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity	
No data available	

Acute dermal toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	AQUASURE+FD Product Item Code: 10112, 10116, 11146, 004002, 10194
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

Acute dermal toxicity	
No data available	
Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	AQUASURE+FD Product Item Code: 10112, 10116, 11146, 004002, 10194
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).
Acute inhalational toxicity	
No data available	
Skin corrosion/irritation	
No data available	
Serious eye damage/irritation	
No data available	
Respiratory or skin sensitisation	
No data available	
Germ cell mutagenicity	
No data available	
Reproduction toxicity	
No data available	
Carcinogenicity	
No data available	
STOT - single exposure	
No data available	
STOT - repeated exposure	
No data available	
Aspiration hazard	
No data available	
Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Vapours and Mist cause irritation effects to the eyes and the respiratory tract. Has a degreasing effect on the skin.	

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)
No data available
Toxicity to fish (chronic)
No data available
Toxicity to Daphnia (acute)
No data available
Toxicity to Daphnia (chronic)
No data available
Toxicity to algae (acute)
No data available
Toxicity to algae (chronic)
No data available
Bacteria toxicity
No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water			
1	xylene	1330-20-7	215-535-7
log Pow		3.12	
Reference temperature		20	°C
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of in agreement with the regional waste disposal company.

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1133
Proper shipping name	ADHESIVES
Tunnel restriction code	D/E
Label	3
Comments	Containers with a capacity <= 450 ltrs are not subject to ADR-regulations (refer to 2.2.3.1.5.)

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1133
Proper shipping name	ADHESIVES
EmS	F-E, S-D
Label	3
Comments	Containers with a capacity <= 30 ltrs are not subjected to IMDG regulations, chapter 4.1, 5.2 and 6.1 (see IMDG-Code 2.3.2.5)

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1133
Proper shipping name	Adhesives
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 3, 40
---	----------

Trade name: AQUASURE+FD

Current version : 3.0.0, issued: 10.01.2019

Replaced version: 2.1.0, issued: 14.09.2018

Region: GB

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	diphenylmethane-4,4'-di-isocyanate	101-68-8	202-966-0	56

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: P5c

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content	25	%
VOC-value	245	g/l

15.2 Chemical safety assessment

No data available.

SECTION 16: Other information
Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH014	Reacts violently with water.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H351	Suspected of causing cancer
H373i	May cause damage to organs through prolonged or repeated exposure if inhaled.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
2	The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, 21107 Hamburg, Germany

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 633442